

# Tabulars with reledmac

October 14, 2015

## Abstract

This file provides example of using tabular environments with *reledmac*.  
We use `edtabularl`, `edtabularc` and `edtabularr`, with `marginal`,  
`critical` and `familiar` notes. We also use optional arguments of `\pstart`.

### 1 Left align

1		linea prima	linea prima	sidenote l
2		linea secunda	linea secunda <sup>1</sup>	
3		linea tertia	linea tertia	
4		linea quarta	linea quarta	
5		linea quinta	linea quinta <sup>1</sup>	
6		linea sexta	linea sexta	

### 2 Center align

7		linea prima	linea prima	sidenote c
8		linea secunda	linea secunda <sup>2</sup>	
9		linea tertia	linea tertia	
10		linea quarta	linea quarta	
11		linea quinta	linea quinta <sup>2</sup>	
12		linea sexta	linea sexta	

### 3 Right align

13		linea prima	linea prima	sidenote r
<hr/>				
		<sup>1</sup> familiar footnote A.		
		<sup>2</sup> familiar footnote A.		
<hr/>				
		<sup>1</sup> familiar footnote B.		
		<sup>2</sup> familiar footnote B.		
<hr/>				
3	tertia ]	critical note A		
9	tertia ]	critical note A		
<hr/>				
4	quarta ]	critical note B		
10	quarta ]	critical note B		

14	linea secunda	linea secunda <sup>3</sup>
15	linea tertia	linea tertia
16	linea quarta	linea quarta
17	linea quinta	linea quinta <sup>3</sup>
18	linea sexta	linea sexta

---

<sup>3</sup>familiar footnote A.

---

<sup>3</sup>familiar footnote B.

---

15 tertia ] critical note A

---

16 quarta ] critical note B