

# Loading multiple data models with biblatex

Maïeul Rouquette  
maieul <at> maieul <dot> net

Version 1.0.0  
25/06/2014

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>	<b>4</b>	<b>Credits</b>	<b>2</b>
<b>2</b>	<b>Use</b>	<b>1</b>	<b>5</b>	<b>Change history</b>	<b>2</b>
<b>3</b>	<b>For developers</b>	<b>2</b>			

## 1 Introduction

Datamodel in biblatex are conceived to be distributed as a part of citations and bibliographic styles<sup>1</sup>. However, sometime, the modification in datamodel is too tiny to need a new style, and can be easily integrated to standard biblatex styles. That is the case in the two projects *biblatex-reauthor* and *biblatex-manuscripts-philology*. Because of biblatex conception of datamodel distribution, it's not possible to load both datamodels of *biblatex-reauthor* and *biblatex-manuscripts-philology*.

This package *biblatex-multiple-dm* allows to load multiple datamodel without creating a full biblatex style.

## 2 Use

The package must be loaded before the biblatex package. It's loaded with two options:

**tools** which is a comma separated list of the datamodels to be loaded.

**bibstyle** which is the main bibstyle to be loaded.

For example:

```
\usepackage[tools={realauthor,manuscripts},bibstyle=verbose]{biblatex-multiple-dm}
```

After that, the biblatex package must be loaded with the bibstyle option equal to multiple-dm:

```
\usepackage[bibstyle=multiple-dm,citestyle=verbose-trad2]{biblatex}
```

---

<sup>1</sup>See: <https://github.com/plk/biblatex/issues/220#issuecomment-37761639>.

### 3 For developers

If one developer wants to allow is “bibliography style” be compatible with biblatex-multiple-dm, he/she has just to try the existing of `\biblatexmultipliedm@bibstyle` macro when loading primary bibstyle:

```
\ifdef{\biblatexmultipliedm@bibstyle}
  {\RequireBibliographyStyle{\biblatexmultipliedm@bibstyle}}
  {\RequireBibliographyStyle{verbose}}
```

### 4 Credits

This package was created for Maïeul Rouquette’s phd dissertation<sup>2</sup> in 2014. It is licensed on the *LaTeX Project Public License*<sup>3</sup>. It’s freely inspired by a code of Oleg Domanov<sup>4</sup>.

All issues can be submitted, in French or English, in the GitHub issues page<sup>5</sup>.

### 5 Change history

#### 1.0.0 2014-06-25

First public release.

---

<sup>2</sup><http://apocryphes.hypothese.org>.

<sup>3</sup><http://latex-project.org/lppl/lppl-1-3c.html>.

<sup>4</sup><http://tex.stackexchange.com/a/154568/7712>.

<sup>5</sup><https://github.com/maieul/biblatex-multiple-dm/issues>.