

Tabulars with reledmac

August 13, 2015

Abstract

This file provides example of using tabular environments with *reledmac*.
We use `edtabularl`, `edtabularc` and `edtabularr`, with marginal,
critical and familiar notes. We also use optional arguments of `\pstart`.

1 Left align

1	linea prima	linea prima	sidenote l
2	linea secunda	linea secunda ¹	
3	linea tertia	linea tertia	
4	linea quarta	linea quarta	
5	linea quinta	linea quinta ¹	
6	linea sexta	linea sexta	

2 Center align

7	linea prima	linea prima	sidenote c
8	linea secunda	linea secunda ²	
9	linea tertia	linea tertia	
10	linea quarta	linea quarta	
11	linea quinta	linea quinta ²	
12	linea sexta	linea sexta	

3 Right align

13	linea prima	linea prima	sidenote r
<hr/>			
	¹ familiar footnote A.		
	² familiar footnote A.		
<hr/>			
	¹ familiar footnote B.		
	² familiar footnote B.		
<hr/>			
3	tertia]	critical note A	
9	tertia]	critical note A	
<hr/>			
4	quarta]	critical note B	
10	quarta]	critical note B	

14	linea secunda	linea secunda ³
15	linea tertia	linea tertia
16	linea quarta	linea quarta
17	linea quinta	linea quinta ³
18	linea sexta	linea sexta

³familiar footnote A.

³familiar footnote B.

15 tertia] critical note A

16 quarta] critical note B